



Apply is a family composed of wall applique, ceiling and bollard, characterized by small size and maximized performance. Apply ceiling is available in square version while Apply wall applique is available in square and rectangular version, both mono or double emission. Apply bollard is able to orient the head of 20° towards the walkway. The entire family is characterized by the total absence of visible screws and the rearward position of the light source guarantee's maximum visual comfort and a clear and sharp lighting effect.

**TECHNICAL DESCRIPTION**

Die-cast aluminium housing, extruded aluminium structure with high corrosion resistance. Nylon black shutter. Toughened transparent glass diffuser. Stainless steel A4 screws. Luminaire supplied with 5,0m neoprene H05RN-F cable. Silicone gaskets. Double powder paint.

**REGISTERED DESIGN**

**PROTECTION CLASS**  
IP65

**ISOLATION CLASS**  
CLASS I ⊕ APPLY SQUARE  
CLASS II ⊞ APPLY RECTANGULAR

**MECHANICAL RESISTANCE**  
IK 06 APPLY BOLLARD  
IK 07 APPLY WALL EFFECT and CEILING

**COLOURS APPLIQUE / CEILING**

- .01** White (black optic)
- .09** Black (black optic)
- .20** Burnished Bronze (black optic)



**COLOURS BOLLARD**

- .09** Black (black optic)
- .20** Burnished Bronze (black optic)




[www.simes.it/apply](http://www.simes.it/apply)



APPLY Square ceiling






**S.2558W** Single emission 120°  
 LED MODULE **3000K** CRI90 987lm 8,6W  
 (on request 2700K CRI90 916lm)  
 (on request 4000K CRI80 1219lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable




APPLY Square applique



**S.2555W** Single emission 120°  
 LED MODULE **3000K** CRI90 987lm 8,6W  
 (on request 2700K CRI90 916lm)  
 (on request 4000K CRI80 1219lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable



**S.2557W** Double emission 120°  
 2 x LED MODULE **3000K** CRI90 987lm 8,6W  
 (on request 2700K CRI90 916lm)  
 (on request 4000K CRI80 1219lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable





SIMES






APPLY Rectangular applique


SIMES




**S.2550W** Single emission 90°  
 LED MODULE 3000K CRI90 455lm 4,0W  
 (on request 2700K CRI90 431lm)  
 (on request 4000K CRI80 564lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable



**S.2552W** Double emission 2x90°  
 2 x LED MODULE 3000K CRI90 455lm 4,0W  
 (on request 2700K CRI90 431lm)  
 (on request 4000K CRI80 564lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable



APPLY Rectangular bollard version with adjustable optic



**S.2560W** Single emission 90°  
 LED MODULE 3000K CRI90 455lm 4,0W  
 (on request 2700K CRI90 431lm)  
 (on request 4000K CRI80 564lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable

